

	<b>GRASIM INDUSTRIES LIMITED</b> UNIT : GRASIM CELLULOSIC DIVISION, VILAYAT, BHARUCH	Doc. No.	CD/VIL/VSF-G019
		Review Date	01.01.2024
		Review due Date	01.01.2027
	<b>Specification</b>	Revision No.	01
		Issue No.	01
		Page No.	Page 1 of 1

**Material Code**      SFBMSF038012ECOT  
**Specification**      VISCOSE STAPLE FIBRE 1.2X38-BM-LIVAECO-FSC Mix Credit

S. No	Parameters	Units	Norms	Test Method
1	Denier	-	1.20 (±0.1)	BISFA
2	Staple Length	mm	38.0(-2 / +1)	GRASIM
3	Conditioned Tenacity	gpd	Min. 3.70	BISFA
4	Wet modulus at 5% Elongation	gpd	Min 0.65	BISFA
5	Conditioned Elongation	%	Min. 13.0	BISFA
5	ISO Brightness	%	Min. 80	GRASIM
6	Finish oil	%	Min.0.25	GRASIM
7	Moisture Regain	%	13.0	FORTE

**Note – Physical Properties to be measured at 27 ± 2 °C and 65±2 % R.H**

**Prepared By**

**Approved By**



**Birla Cellulose**  
Fibres from nature